

# Seemee Loop

## Frontlit

### Main applications

- Billboards
- Banners
- Roll ups

### Major advantages

- Very good adhesion for bright color
- Printable with UV & Latex inks
- Weldable with high frequency & hot bar systems
- Made in Germany

	■ Technical properties	Standards
Weight	330 g/m <sup>2</sup> • 9.7 oz/sqyd	EN ISO 2286-2
Widths	470 cm • 185 inches - 235 cm • 92.5 inches	EN ISO 2286-1
	■ Length of the rolls	
Standard format length	50 lm • 54.6 yds	
	■ Physical properties	
Tensile strength (warp/weft)	500/500 N/5cm	EN ISO 1421
Tear strength (warp/weft)	100/100 N	DIN 53.363
	■ Flame retardancy	
Rating	DIN 4102-1 (in progress) EN 13501-1 (in progress) NFPA 701-2015 (in progress)	
	■ Management systems	
Quality		ISO 9001
Environment		ISO 14001
Energy		ISO 50001
	■ Certifications	



The technical data above are averaged values with a +/- 10% tolerance. The buyer of our products is fully responsible for their application or their transformation concerning any possible third party. The buyer of our products is responsible for their implementation and installation according to the standards, use and customs and safety rules of the countries where they are used. For information on our contractual warranty, please refer to the relevant terms and conditions. The values quoted above represent results of tests performed in compliance with common design practices and are provided for only to enable customers to make the best use of our products. Our products are subjects to evolutions due to technical progress, we remain entitled to modify the characteristics of our products at any time. The buyer of our products is responsible for checking the validity of the above data.