

We BRIGHTEN Your BRANDS

ColorLINE

Neon-inspired tubing

- **NEW** Classic colors retain hue in daytime
- Standard colors revert to neutral, frosted white when non-illuminated
- Slim profile similar to standard neon
- High impact acrylic: UV stable, hydrocarbon insensitive, and non-fading
- Convenient, weatherproof connectors between sections
- Can be cut in the field¹

SPECIFICATIONS

Part number	0.6-m Tube701800-Color-2
	1.2-m Tube.....701800-Color-4
	1.8-m Tube701800-Color-6
	2.4-m Tube701800-Color-8
Dimensions	Width.....11 mm
	Base width.....15 mm
	Height.....25 mm
	Lengths.....0.6 m; 1.2 m; 1.8 m; 2.4 m
Factory bends	245 mm radius (radial and flat bend)
In-field bends	Radial bend.....5.8 m
	Flat bend.....1.8 m
Operating temperature	-40° C to +70° C
Protection class	IP66
Power per meter	7.5 W
Power capacity	7.3 m per SloanLED 60 W 12 VDC power supply
Colors	StandardRed, Orange, Yellow, Green, Blue, White, Warm White
	ClassicRuby Red, Citrus Orange, Noviol Gold, Emerald Green, Bromo Blue
Mounting	Dual-position mounting clips (400381-25) orient in two directions



Mounting Clip
400381-25

Accessories..... Snap-on, frosted joint covers (701807) for clean finish
Illuminated, mitered corners:
Inside corner701800-IC-Color
Outside corner701800-OC-Color
Step corner701800-SC-Color

Part number	Item description	Approx. cut increments ¹	Actual length
Standard colors			
701800-X-2	0.6-m Tube	60 mm	626 mm
701800-X-4	1.2-m Tube	60 mm	1236 mm
701800-X-6	1.8-m Tube	60 mm	1846 mm
701800-X-8	2.4-m Tube	60 mm	2455 mm
Classic colors			
701800C-X-2	0.6-m Tube	60 mm	626 mm
701800C-X-4	1.2-m Tube	60 mm	1236 mm
701800C-X-6	1.8-m Tube	60 mm	1846 mm
701800C-X-8	2.4-m Tube	60 mm	2455 mm

NOTE: **X** = desired color. **R** = Red/Ruby Red, **O** = Orange/Citrus Orange, **Y** = Yellow/Noviol Gold, **G** = Green/Emerald Green, **B** = Blue/Bromo Blue, **W** = White, **WW** = Warm White.



¹ After cutting a custom length, any piece with black and red wires protruding from original end cap will still light.

ColorLINE is covered by US and foreign patents pending and covered by the following US patents issued: 6,776,504, 6,969,179, and 7,192,157

SloanLED Headquarters
5725 Olivias Park Drive • Ventura, California 93003
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.
Overslagweg 7 • 2645 EK Delfgauw • The Netherlands
+31 88 12 44 900 • Europe@SloanLED.com

SloanLED.com

© 2017 SloanLED Rev D 2017-04-12

 **SloanLED**[®]
Leaders in LED Technology