

# 300T1 300 W Power Supply

Damp/Dry-rated 300 Watt power supply

- Universal input voltage – 100-277 VAC, 50-60 Hz input
- Constant voltage output at 24 V and three outputs at 96 W (288 W total)
- Auto-resetting – No fuses to replace or circuit breaker to reset – Short circuit and over-current protection automatically resets when short condition is corrected
- Rugged and compact



## Specifications

<b>Part number</b> .....	701895-300T1
<b>Dimensions L x W x H</b> .....	389 mm x 130 mm x 38 mm (15.3 in x 5.12 in x 1.5 in)
<b>Nominal input voltage</b> .....	100-277 VAC, 50-60 Hz
<b>Maximum input current</b> .....	4 A
<b>Power output</b> .....	3 x 96 W @ 24 VDC
<b>Protection class</b> .....	IP54
<b>Location rating</b> .....	Dry and damp locations
<b>Operating temperature</b> .....	-40° C to +60° C, derate to 50% of max load at +70° C
<b>Weight</b> .....	3.15 kg (6.95 lbs)
<b>Compatibility</b> .....	SloanLED 24 VDC products



**SloanLED Headquarters**  
805.676.3200 • info@SloanLED.com

**SloanLED Europe b.v.**  
+31 88 12 44 900 • Europe@SloanLED.com



**SloanLED.com**

© 2019 SloanLED Rev B 2019-10-16

Specifications subject to change without notice.

 **SloanLED®**  
Leaders in LED Technology