



The burning master

Proven design – fuel versatility – highest efficiency

The POLFLAME® multifuel burner incorporates numerous innovative design ideas of ultra-modern pyroprocessing technology. Depending on the process-technological requirements, the burner is designed for **fossil fuels** such as coal, anthracite, oil, petcoke and natural gas or for the use of **solid and liquid substitute fuels** such as animal meal, sewage sludge, solid shredded waste, waste material, wood, biomass, production residues etc.

The unique patented burner design allows a high and precisely adjustable supply of air/oxygen to the heart of the flame. This ensures reliable ignition, good burnout of the materials used and low pollutant emissions. Furthermore, it is possible to substitute fossil fuels to a large extent by other fuels.

Due to the variable nozzle adjustment system, the flame shape of the POLFLAME® can be adapted continuously and within a wide range to the requirements of product quality, irrespective of the type of fuel. The design of the nozzle adjustment system and of the burner tip ensures that the adjustment mechanism functions reliably during operation even after a long period of use.

The innovative design of the new POLFLAME® thus provides outstanding process-technological product features for a variety of different fuels.

The POLFLAME® is therefore highly attractive, not only for new plants but also for system replacements in the course of plant upgrades, either as an individual component or in combination with the POLYTRACK® cooler.

POLFLAME® Burner



thyssenkrupp

Fields of application

Main firing system of rotary kiln systems for:
coal, lignite, coke, anthracite coal, wood dust, meat or bone meal, solid
wastes, heavy and light oil, waste oil, natural gas

Main features

Variable adjustment of flame length, flame shape and temperature
distribution during operation

Complete combustion of different fuels in the rotary kiln

High rate of fossil fuel substitution by secondary fuels

Constant flame stability at different burner settings

Easy operability

Reproducible setting of the flame shape depending on kiln operating
conditions and type of fuel

Modular nozzle design

Design parameters

Thermal Power: 10 to 300 MW

Kiln capacities: 1.000 to 12.000 tpd (e.g. cement)

Adjustable swirl and divergence of the flame:

Swirl: 10° to 40°

Divergence: -5° to 15°

Contact

thyssenkrupp Industrial Solutions AG

Graf-Galen-Straße 17

59269 Beckum, Germany

Phone: +49 2525 99-0

E-mail: pyro.tkis@thyssenkrupp.com

www.thyssenkrupp-industrial-solutions.com/pyroprocessing

Sales Agent

© 2016 Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustration purposes only. The operation values are considered to be approximate and will be finally determined on the basis of the specific task and the material characteristics. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and thyssenkrupp makes no other warranty of accuracy, reliability, completeness, merchantability or fitness for any purpose, express or implied. Products and services listed may be trademarks, service marks or trade-names of thyssenkrupp and/or its subsidiaries in Germany and other countries. All rights are reserved.