

Sealants for industry

A new range from thyssenkrupp Materials (UK)



Neutral curing silicone. Excellent adhesion on glass, treated wood, PVCu and aluminium. Fast curing time. BS 5889 type A.



Silicone sealant based on an acetoxycuring system. Excellent adhesion on anodised aluminium, glass and metals. BS 5889 type B.



Low modulus PU sealant for use on a vast range of materials. Maximum movement capacity: 30%.



Medium modulus for structural bonding (mechanical fixing not necessary). Very fast curing time. Can be sanded.



Fast curing high modulus adhesive based on MS polymers. Highly suitable for bonding on a vast range of materials.



Medium modulus adhesive sealant based on hybrid polymers, for general application in the building industry.

Central Region Sales Office

Tel: 01384 563 900
Fax: 01384 563 191

Northern Region Sales Office

Tel: 0844 257 0340
Fax: 0844 257 0331

South West Region Sales Office

Tel: 01793 767 676
Fax: 01793 767 654

Camberley Sales Office

Tel: 01276 673 173
Fax: 01276 673 189

Milton Keynes Sales Office

Tel: 0844 257 0337
Fax: 0844 257 0336

Northern Ireland Sales Office

Tel: 0844 326 7300
Fax: 0844 326 7320

sales.tkmuk@thyssenkrupp.com
www.thyssenkrupp-materials.co.uk

engineering.tomorrow.together.



thyssenkrupp