

## Declaration of Performance

### N° 0101/002 rel.3

Identification code of the product-type	Welded tube made of non-alloy structural steel S275J0H/1.0149 in accordance with EN10219:2006.
Identification of the construction product	In accordance with the information included in the identification label with barcode and/or bundle number and in the inspection certificate.
Intended use of the construction product	Cold formed welded structural hollow sections of circular, square, or rectangular shape formed cold without subsequent heat treatment.
Manufacturer (registered office)	<b>Marcegaglia Carbon Steel</b> Via Bresciani, 16 – 46040 Gazoldo degli Ippoliti (MN) – Italia
Production plant	<b>Gazoldo Degli Ippoliti</b> Via Bresciani, 16 – 46040 Gazoldo Degli Ippoliti (MN) - Italia
System of assessment and verification of constancy of performance of the construction product	<b>2+</b>
Name and identification number the notified body	RINA Service S.p.A. – Via Corsica, 12 – 16128 Genova - Italia <b>0474</b>

Notified factory production control certification body performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and issued the certificate of conformity of the factory production control.

#### Declared Performance

Essential Characteristic		Performance		Harmonised Technical specification
Tolerances on dimensions and shape	Round, square and rectangular section	In accordance with EN10219:2006		EN10219-1:2006
Durability (chemical composition)	Nominal thickness (mm)	Values		
	>                      ≤	-	max (%)	
	-                      16	C: 0,20                      P: 0,035	S: 0,035	
		Mn: 1,50                      N: -		
Yield strength	Nominal thickness (mm)	Values		
	>                      ≤	min (MPa)	max (MPa)	
	-                      16	275	-	
Tensile strength	Nominal thickness (mm)	Values		
	>                      ≤	min (MPa)	max (MPa)	
	-                      3	430	580	
	3                      16	410	560	
Elongation (b,c)	Nominal thickness (mm)	Values		
	>                      ≤	min (%)	max (%)	
	-                      16	20	-	
Impact strength (a,d)	Nominal thickness (mm)	Values		
	>                      ≤	min (J)		
	-                      16	27 at 0°C	-	
Weldability CEV	Nominal thickness (mm)	Values		
	>                      ≤		max (%)	
	-                      16	-	0,40	
<small>           a. Impact properties are verified only when option 1.3 is specified.            b. For section sizes D/T &lt; 15 (round) e (B+H)/2T &lt; 12.5 (square and rectangular) the minimum elongation is reduced by 2.            c. For thicknesses &lt; 3.0 mm the percentage elongation may be reported for a gauge length of 80 mm or 50 mm            d. Impact test, when applicable or required, shall be carried out in accordance with EN10219-1. Impact test is not required for specified thicknesses &lt; 6 mm.         </small>				

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of Marcegaglia Carbon Steel by:



Arnaldo Ing. Barini  
 Direttore dello Stabilimento di Gazoldo Degli Ippoliti  
 Gazoldo Degli Ippoliti 02/11/2015

*This declaration of performance is valid only in presence of the material identification label and the waybill or the inspection certificate issued after delivery.*

